



DEXTER
LAUNDRY

Commercial Maxi Load T-750 Express Washer

(Model Model
WCAD50KCS-12SZ)



Maxi Load T-750 Express Washer

Dexter washers are engineered for the laundry owner demanding greater efficiency, performance and programming capabilities.

Commercial Design

- **Save water** with "sump free" design
- **304 Stainless Steel** keeps Dexter washers looking good
- **Heavy-duty** Sur-Coat Frame is built to last like a battleship
- **Over-sized bearings and seals** run smooth and add to machine life

VFD Technology

- **Reduce installation cost** by using single or three phase power
- **Extend motor life** by ramping current inrush
- **Save electricity** with lower running amperage draw
- **Lower electricity** demand by eliminating spike usage

200 G-Force Extraction

- **Save drying energy** with 200 G-Force extraction
- **Enhance customer turnover** with better washer and dryer performance
- **Achieve consistent results** throughout all washer sizes

Powerful Controls

- **Palm OS®** with built-in infrared port
- **Save programming time** using a handheld computer running optional Palm OS® software
- **Easily customize** pricing, cycles, water temps, supply inputs and more
- **Offer plus cycle**, time of day, and tiered pricing
- **Network capable** with included communication port

Customer Friendly Design

- **Large, easy to use door** for convenient loading and unloading
- **Easy-to-read digital display** including cycle time remaining information
- **Soft touch cycle selection buttons** with temperature icons
- **Ultra-quiet machine operation** improves the laundry environment



Commercial T-750 Express Washer

Capacity

Load Specification	Maxi Load	
Dry Weight Capacity	50 lbs	22.6 kg
Cylinder Diameter	30"	76.2 cm
Cylinder Depth	16"	40.64 cm
Cylinder Volume	6.5 cu ft	184.1 dm ³

Dimensions

Cabinet Height	54"	137.16 cm
Cabinet Width	34.375"	87.35 cm
Overall Depth	32.25"	81.92 cm
Floor to Door Bottom	18"	45.72 cm
Door Opening	19.25"	48.90 cm

Washing/Extraction

High Extract Speed	200 G-Force	685 RPM
Intermediate Extract Speed	60 G-Force	375 RPM
Washing Speed	43 RPM	
Motor Size	3 HP	2.25 kw

Electrical

Electrical Phase	Single or Three	
Electrical Voltage (60 Hz)	208-240	
Electrical Running (Amps)	8.4	
Circuit Protection (Amps)	20 amp*	
Electrical Wire Size	12 gauge	
Electrical Service (Single Phase)	2 wire + ground	
Electrical Service (Three Phase)	3 wire + ground	

Water

Average Water Usage	49 gal	196.84 L
Maximum Hot Water Usage	19 gal	79.49 L
Water Inlet Size	3/4"	19 mm
Water Flow Rate (per minute)	9 gal	34.06 L
Water Pressure (min/max)	30-120 psi	207-827 Kpa
Drain Diameter (O.D.)	3"	7.62 cm
Floor to Center of Drain	7"	17.78 cm

Installation

Net Weight	986 lbs	447.2 kg
Clearance Between Machines	1/2" (min)	1.27 cm
Clearance Behind Machines	24" (min)	60.96 cm
Concrete Thickness	8" (min)	20.32 cm

* For elevations above 6600 feet or for very hot climates, a 30 amp breaker is recommended due to downrating of circuit breakers under these conditions.



DEXTER
LAUNDRY

Dexter Laundry, Inc.
2211 W. Grimes, Fairfield, Iowa 52556
www.dexterlaundry.com
1-800-524-2954

© 2009, Dexter Laundry, Inc.
Dexter reserves the right to change features or specifications without notice.



Available with coin drop, programmable electronic drop or Easy Card™.



Easy Programming



Large Loading Door



Emergency Stop Button