

# On- Premise 30-Cycle Washer Family

Product Model	T-600 -Maxi Load		T-900 - Mega Load		T-1200 - Magnum Load	
	WCND40HCX- __		WCND60HCX- __		WCND80HCX- __	
Dry Weight Capacity - lb (kg)	40lb	(18.2kg)	60lb	(27.2kg)	80lb	(36.3kg)
Cabinet Height - in (cm)	49.75"	(126.4cm)	55.5"	(141.0cm)	58"	(147.3cm)
Cabinet Width - in (cm)	29.88"	(75.9cm)	34.39"	(87.4cm)	34.39"	(87.4cm)
Overall Depth - in (cm)	36"	(91.4cm)	38.75"	(98.4cm)	45.25"	(114.9cm)
Floor to Door Bottom - in (cm)	16"	(40.6cm)	16.13"	(41.0cm)	19"	(48.3cm)
Door Opening - in (cm)	15.25"	(38.7cm)	19.25"	(48.9cm)	19.25"	(48.9cm)
Cylinder Diameter - in (cm)	25"	(63.5cm)	30"	(76.2cm)	30"	(76.2cm)
Cylinder Depth - in (cm)	21.13"	(53.7cm)	22"	(55.9cm)	28"	(71.2cm)
Cylinder Volume - cu.ft. (liters)	6.0cu.ft.	(170.1l)	9.0 cu.ft.	(255.1l)	11.5cu.ft.	(326.0l)
Water Inlet Size - in (mm)	3/4"	(19mm)	3/4"	(19mm)	3/4"	(19mm)
Water Flow Rate - gal/min (l/min)	9 g/m	(34.1l/m)	9 g/m	(34.1l/m)	12 g/m	(45.4l/m)
Water Pressure - (min/max)	30-120psi	(207-827kPa)	30-120psi	(207-827kPa)	10-130psi	(69-896kPa)
Drain Diameter (OD) - in (cm)	3"	(7.6cm)	3"	(7.6cm)	3"	(7.6cm)
Floor to Drain Center - in (cm)	5"	(12.7cm)	7.5"	(19.1cm)	8"	(20.3cm)
Speeds: G-Force (RPM)						
Wash	.9G	(50RPM)	.9G	(43RPM)	.9G	(43RPM)
Intermediate Extract	60G	(412RPM)	60G	(375RPM)	60G	(375RPM)
High Extract	100G	(532RPM)	140G	(573RPM)	100G	(485RPM)
Motor Size - HP (Kw)	2HP	(1.5Kw)	3HP	(2.24Kw)	3HP	(2.24Kw)
Electrical:						
Circuit Breaker/Running Amps/Wire Size						
-10 (120/60/1)		---		---		---
-12 (208-240/60/1 - 2 wire + ground)		15amp / 6.2amp / #12		20amp / 8.4amp / #12		20amp / 8.4amp / #12
-12 (208-240/60/3 - 3 wire + ground)		15amp / 6.2amp / #12		20amp / 8.4amp / #12		20amp / 8.4amp / #12
-59 (230/50/1 - 2 wire + ground)		15amp / 6.2amp / 3.5mm2		20amp / 8.4amp / 3.5mm2		20amp / 8.4amp / 3.5mm2
Installation Recommendations:						
Clearance Between Machines - in (cm)	1/2"	(1.3cm)	1/2"	(1.3cm)	1/2"	(1.3cm)
Clearance Behind Machines - in (cm)	24"	(61.0cm)	24"	(61.0cm)	24"	(61.0cm)
Concrete Thickness - in (cm)	6"	(15.2cm)	8"	(20.3cm)	8"	(20.3cm)
Net Weight	558lbs	(253.1kg)	959lbs	(435.0kg)	1060lbs	(480.8kg)
Shipping Weight	587lbs	(266.3kg)	992lbs	(450.0kg)	1099lbs	(498.5kg)
Shipping Dimensions:						
Height - in (cm)	54.75"	(150.2cm)	60.75"	(150.2cm)	63"	(160.0cm)
Width - in (cm)	31.5"	(80.1cm)	36"	(91.44cm)	36"	(91.4cm)
Depth - in (cm)	41"	(104.1cm)	44.25"	(112.4cm)	52.14"	(132.7cm)
Approvals**	UL / CE		UL / CE		UL / CE	

\* 3 Bath cycles, 22 minutes total

\*\* Agency approvals may vary depending on configuration. Consult factory for details.

For the most accurate information, please consult machine installation guide for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change.



**Dexter Laundry, Inc.**

2211 W. Grimes, Fairfield, Iowa 52556

[www.dexterlaundry.com](http://www.dexterlaundry.com)

1-800-524-2954



## Product Reference Sheet Dexter On-Premise 30-Cycle Washer

# 40lb, 60lb, and 80lb Models

### Dexter Non-Express Washers with 30-Cycle Microprocessor

For laundry managers who need greater programming flexibility Dexter Laundry offers a range of our larger capacity non-Express models with a more powerful 30-cycle microprocessor control. This control features 29 popular on-premise laundry programs and features 10 easy-to-read LED status lights. This control also allows laundry managers to quickly and easily modify the most popular parameters of any cycle, and to save them for future use.

- Cycle Time – for each wash or rinse (up to 9 baths, 0-30 minutes)
- Bath Temperature – Specific Temperature, with capability for electric or steam heat
- Water Level – High, Low, Empty
- Spin Time – up to 10 minutes
- Injection Source – 4 supplies plus combinations of 1-4

These models also feature key lock access to control who makes programming changes on your equipment, and diagnostic and test cycles make troubleshooting quick and easy when the need arises.

Like our 6-cycle models, laundry managers don't need to settle for less when it comes to quality and durability. All 30-cycle models feature the rugged construction and durability that Dexter is famous for:

- 304 Stainless steel inner cylinder, outer tub, top, front, and side panels
- Heavy duty welded base frame made of structural steel

- Over-size shaft and permanently lubricated bearings
- Long lasting, soft-touch cycle selection buttons
- Backed by the strongest warranty in the industry

If your laundry operation needs an economical solution with greater programming flexibility, Dexter 30-cycle models are a great choice if you are looking for great performance and years of reliable, trouble-free service.

