

On- Premise 6-Cycle Washer Family

Product Model	T-300 - Double Load WCVD20HCX - _ _	T-400 - Triple Load WCVD30HCX - _ _	T-600 - Maxi Load WCVD40HCX - _ _	T-900 - Mega Load WCVD60HCX - _ _	T-1200 - Magnum Load WCVD80HCX - _ _
Dry Weight Capacity - lb (kg)	20lb (9.0kg)	30lb (13.6kg)	40lb (18.2kg)	60lb (27.2kg)	80lb (36.3kg)
Cabinet Height - in (cm)	43.88" (111.4cm)	48.25" (122.6cm)	49.75" (126.4cm)	55.5" (141.0cm)	58" (147.3cm)
Cabinet Width - in (cm)	26" (66.0cm)	29.88" (75.9cm)	29.88" (75.9cm)	34.39" (87.4cm)	34.39" (87.4cm)
Overall Depth - in (cm)	24.81" (63.0cm)	27.38" (69.5cm)	36" (91.4cm)	38.75" (98.4cm)	45.25" (114.9cm)
Floor to Door Bottom - in (cm)	15" (38.1cm)	16" (40.6cm)	16" (40.6cm)	16.13" (41.0cm)	19" (48.3cm)
Door Opening - in (cm)	12.25" (31.1cm)	15.25" (38.7cm)	15.25" (38.7cm)	19.25" (48.9cm)	19.25" (48.9cm)
Cylinder Diameter - in (cm)	21" (53.3cm)	25" (63.5cm)	25" (63.5cm)	30" (76.2cm)	30" (76.2cm)
Cylinder Depth - in (cm)	13.5" (34.3cm)	14.13" (35.9cm)	21.13" (53.7cm)	22" (55.9cm)	28" (71.2cm)
Cylinder Volume - cu.ft. (liters)	2.71cu.ft. (76.7l)	4.0cu.ft. (113.4l)	6.0cu.ft. (170.1l)	9.0cu.ft. (255.1l)	11.5cu.ft. (326.0l)
Water Inlet Size - in (mm)	3/4" (19mm)	3/4" (19mm)	3/4" (19mm)	3/4" (19mm)	3/4" (19mm)
Water Flow Rate - gal/min (l/min)	9 g/m (34.1l/m)	9 g/m (34.1l/m)	9 g/m (34.1l/m)	9 g/m (34.1l/m)	12 g/m (45.4l/m)
Water Pressure - (min/max)	30-120psi (207-827kPa)	30-120psi (207-827kPa)	30-120psi (207-827kPa)	30-120psi (207-827kPa)	10-130psi (69-896kPa)
Drain Diameter (OD) - in (cm)	2.25" (5.7cm)	3" (7.6cm)	3" (7.6cm)	3" (7.6cm)	3" (7.6cm)
Floor to Drain Center - in (cm)	6" (15.2cm)	5" (12.7cm)	5" (12.7cm)	7.5" (19.1cm)	8" (20.3cm)
Speeds: G-Force (RPM)					
Wash	.9G (55RPM)	.9G (50RPM)	.9G (50RPM)	.9G (43RPM)	.9G (43RPM)
Intermediate Extract	60G (449RPM)	60G (412RPM)	60G (412RPM)	60G (375RPM)	60G (375RPM)
High Extract	100G (579RPM)	100G (532RPM)	100G (532RPM)	100G (485RPM)	100G (485RPM)
Motor Size - HP (Kw)	1HP (.75Kw)	2HP (1.5Kw)	2HP (1.5Kw)	3HP (2.24Kw)	3HP (2.24Kw)
Electrical:					
Circuit Breaker/Running Amps/Wire Size					
-10 (120/60/1)	20amp / 13amp / provided	---	---	---	---
-12 (208-240/60/1 - 2 wire + ground)	15amp / 4amp / #12	15amp / 6.2amp / #12	15amp / 6.2amp / #12	20amp / 8.4amp / #12	20amp / 8.4amp / #12
-12 (208-240/60/3 - 3 wire + ground)	15amp / 4amp / #12	15amp / 6.2amp / #12	15amp / 6.2amp / #12	20amp / 8.4amp / #12	20amp / 8.4amp / #12
-59 (230/50/1 - 2 wire + ground)	15amp / 4amp / 3.5mm2	15amp / 6.2amp / 3.5mm	15amp / 6.2amp / 3.5mm2	20amp / 8.4amp / 3.5mm2	20amp / 8.4amp / 3.5mm2
Installation Recommendations:					
Clearance Between Machines - in (cm)	1/2" (1.3cm)	1/2" (1.3cm)	1/2" (1.3cm)	1/2" (1.3cm)	1/2" (1.3cm)
Clearance Behind Machines - in (cm)	24" (61.0cm)	24" (61.0cm)	24" (61.0cm)	24" (61.0cm)	24" (61.0cm)
Concrete Thickness - in (cm)	6" (15.2cm)	6" (15.2cm)	6" (15.2cm)	8" (20.3cm)	8" (20.3cm)
Net Weight	309lbs (140.2kg)	433lbs (196.4kg)	558lbs (253.1kg)	961lbs (435.9kg)	1060lbs (480.8kg)
Shipping Weight	337lbs (152.9kg)	456lbs (206.8kg)	587lbs (266.3kg)	994lbs (450.9kg)	1099lbs (498.5kg)
Shipping Dimensions:					
Height - in (cm)	50" (53.5cm)	53.5" (136.5cm)	54.75" (150.2cm)	60.75" (154.3cm)	63" (160.0cm)
Width - in (cm)	27.25" (69.2cm)	31.5" (80.0cm)	31.5" (80.1cm)	36" (91.44cm)	36" (91.4cm)
Depth - in (cm)	30.5" (77.4cm)	33.5" (85.1cm)	41" (104.1cm)	45.25" (114.9cm)	52.14" (132.7cm)
Approvals**	UL / CE	UL / CE	UL / CE	UL / CE	UL / CE

** Agency approvals may vary depending on configuration. Consult factory for details.

For the most accurate information, please consult machine installation guide for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change.



Dexter Laundry, Inc.

2211 W. Grimes, Fairfield, Iowa 52556

www.dexterlaundry.com

1-800-524-2954



Product Reference Sheet Dexter On-Premise 6-Cycle Washer

**20lb, 30lb, 40lb,
60lb, and 80lb
Models Available**

Dexter Non-Express Washers with 6-Cycle Microprocessor

Dexter Laundry offers today's laundry managers a wide range of choices in capacity, performance, and programming flexibility all with the same rugged construction and reliability Dexter is famous for. Laundry managers on a tight budget looking for an economical solution for their on premise laundry operation, will want to consider our 6-cycle, non-Express models which offer tremendous value. All models feature our flexible, but easy-to-use basic 6-cycle microprocessor control. This control comes standard with 6 preset cycles, but also gives laundry managers the ability to quickly and easily modify the most popular parameters (listed below) of any cycle, and to save that cycle for future use.

- Cycle Time – for each wash or rinse (up to 8 baths, 0-15 minutes)

- Bath Temperature – Hot, Warm, Cold, no water
- Water Level – High, Low, Empty
- Spin Time – up to 10 minutes
- Injection Source – 4 supplies plus combinations of 1-4

For ease of programming, Dexter 6-cycle washers feature wireless infra-red communication and Palm programming capability to make programming changes fast and easy. These models also feature key-lock access to control who makes programming changes on your equipment.

When considering models with basic performance, laundry managers don't need to settle for less when it comes to quality and durability. All Dexter

models feature the rugged construction and durability that Dexter is famous for:

- 304 Stainless steel inner cylinder, outer tub, top, front, and side panels
- Heavy duty welded base frame made of structural steel
- Over-size shaft and permanently lubricated bearings
- Long lasting, soft-touch cycle selection buttons
- Backed by the strongest warranty in the industry

By investing in Dexter non-Express washers for your laundry, you are choosing a long lasting, and highly economical solution for your on-premise laundry needs.

