



DEXTER
LAUNDRY

DEXTER LAUNDRY

ON-PREMISE LAUNDRY CATALOG



DEXTER.COM



WHEN YOUR BUSINESS DEPENDS ON LAUNDRY, YOU CAN DEPEND ON DEXTER.

We know there's more to your business than laundry. That's why Dexter Laundry offers a full-line of on-premise laundry solutions that you can depend on. Our state-of-the-art controls and management software puts you in control of your laundry. This gives you the confidence to manage your business, while we help to manage your laundry.

For over 125 years, Dexter Laundry has been helping people and companies around the world process laundry faster and more efficiently. Dexter products can be found in a variety of laundries, including hotels, nursing homes, animal care facilities, sports stadiums, religious centers and many more. Laundry managers in these locations have learned from experience that Dexter washers and dryers are designed to show-up cycle after cycle, year after year, in even the harshest laundry environments.

Our relationship doesn't end once the sale is complete. We stand behind every machine we build because we are passionate about creating the best laundry ownership experience we can. Every Dexter machine is backed by an industry-leading warranty and lifetime technical support. We are proud to partner with our Dexter Authorized Distributors worldwide to ensure that you get the best service possible.

WHEN YOUR BUSINESS DEPENDS ON LAUNDRY, YOU CAN DEPEND ON DEXTER.

THE DEXTER ADVANTAGE



As employee-owners, our long-term success depends on your long-term success. Our focus in every product we build, and every service we provide, is to make managing and processing your laundry easier. We do this by designing products that will live up to your expectations of high quality and we confidently stand behind every machine you invest in. That's the **DEXTER ADVANTAGE** - the confidence you need to run your business.



OUR COMPANY

Dexter Laundry has been helping people and customers around the world process laundry faster and more efficiently for over 125 years. All of our products are designed, built, and assembled in the USA at our headquarters in Fairfield, Iowa. As an employee-owned company, our personal success depends on yours, and we're committed to building better businesses together.

OUR PRODUCTS

Every Dexter product is designed and built to ensure that it will withstand even the harshest laundry environments. We refuse to compromise on the engineering or quality of materials that we put into every machine. To provide the highest quality and reliability, we believe that every Dexter-branded product should be made by us.



OUR PROMISE

Here at Dexter, we're committed to helping you keep your business running. You're welcome to contact our team before, during, and after your laundry investment. We're here to help and happy to guide you along the way. As further proof of this commitment, every Dexter product comes with an industry-leading warranty and lifetime technical support.

OUR INDUSTRIES

Dexter washers and dryers are found in successful laundries worldwide. Our vended equipment can be found in some of the world's largest laundromats, and our on-premise products are found in a variety of laundry environments. From hospitals to dairy farms, fire houses to battle ships, metropolitan cities to remote villages, our products can handle them all.



ON-PREMISE PRODUCT DETAILS

We know that there’s more to your business than laundry. That’s why we’re committed to helping you achieve long term success by providing a full line of on-premise laundry solutions you can depend on. Our products will provide you the flexibility, performance, and durability you need to process your laundry fast and efficiently. All of our products are engineered, manufactured, and tested to ensure that they show up for work in even the harshest laundry environments. With lifetime technical support and industry leading warranties, you can be confident that we stand behind every machine.

“DEXTER MACHINES ARE WORTH THE INVESTMENT, THEY COME WITH A HIGH LEVEL OF SERVICE & EXPERTISE.”

“THE DEXTER MACHINES ARE MADE WITH SUPERB QUALITY IN MIND. THE COST EFFECTIVENESS HAS BEEN OUTSTANDING.”

“THE QUALITY OF THE MACHINES IS WHAT SOLD ME, THEY JUST WORK...”



WASHER PRODUCT DETAILS

DURABLE

With heavy-duty bearings in a cast iron bearing housing, a welded steel spider and shaft, and a rugged frame design that has been proven over two decades, Dexter washers are built to last.

Every model is designed to withstand our extreme 1,000 hour out-of-balance test.

The polished chrome doors and 304 stainless steel tub, cylinder, top, front, and side panels keep washers looking great year after year.

EFFICIENT

Perforated cylinders and raised baffles create superior wash action, while the efficient washer design saves water on every cycle.

The automatic chemical injection feature allows for the perfect combination of chemicals and helps protect your staff from harmful substances.

An option of 100 g-force or powerful Express 200 g-force extraction helps remove water and reduce dry time.

FLEXIBLE

O-Series controls give you the precision you need to get your laundry done right while still being simple to use. Easy programming is available with DexterLive.com.

The 6-cycle control is a simple control with six preset cycles that are programmable to fit your laundry needs.

Our electronic pressure sensor offers a range of water level options to increase efficiency and help save on water expenses.

RELIABLE

Our industry-leading 10-year warranty covers the frame, tub, cylinder, shaft, seals, bearings, and bearing housing.

A 3-year parts warranty covers the rest.

We stand behind every machine you invest in with lifetime technical support.

INSTALLATION

Adjustable final extract speeds and other customizable options allow Dexter washers to fit most installations.

Most Dexter washers fit through a standard 36” doorway.

Most Dexter washers can be installed with either single or three phase power.

OPTIONS

O-Series controls are available with 200 g-force extract speed.

6-Cycle controls are available in 100 and 200 g-force extraction.

Some O-Series models are also available with electric heat and steam heat options.

DRYER PRODUCT DETAILS

DURABLE

With heavy-duty bearings in cast iron bearing housings and fully welded and painted cabinets, Dexter dryers are built to last.

Using proven washer-style technology, welded steel spider assemblies support the tumbler from the rear and eliminate the need for front support rollers.

Formed in tumbler baffles are strong and stable while providing great tumbling action.

EFFICIENT

O-Series dryers offer Moisture Detection with wireless sensing technology which reduces dry time; saving energy and prolonging the life of your linens.

Perforated tumblers and balanced radial airflow provide maximum efficiency.

The anti-wrinkle feature offers an intermittent tumble to keep laundry wrinkle free.

FLEXIBLE

O-Series controls give you the precision you need to get your laundry done right while still being simple to use. Easy programming is available with DexterLive.com.

The 6-cycle control is a simple control with five preset cycles and one temporary cycle to fit your laundry needs.

The reversible door option on all on-premise single dryers allows for a more ergonomic set up when needed.

RELIABLE

Our industry leading 5-year warranty covers the trunnion, bearings, and bearing housing.

A 3-year parts warranty covers the rest.

O-Series dryers offer the Dexter Fire Response System. If an unexpected rise in temperatures occurs the machine will take action to help protect your facility.

INSTALLATION

Vertical exhaust and venting come standard on every dryer for easy installation.

The exhaust cleanouts are easy to reach and allow for regular maintenance.

The hinged lower service door on single dryers makes cleaning the lint screen quick and easy.

OPTIONS

Stainless or galvanized tumblers and white or stainless steel panels are available on most models.

Available with 6-cycle or O-Series controls.

Choose between gas models or electric models. Propane kits also available.

Options for reversing models and Fire Response are available.

WITH DEXTER O-SERIES YOU HAVE TOTAL CONTROL OVER YOUR BUSINESS AND YOUR LAUNDRY.

Our easy to use O-Series controls give you the precision and features you need to ensure your laundry is done properly. With detailed technology and reporting systems, you have the tools needed to limit downtimes and keep your laundry running efficiently. This gives you more time to take care of your business, not your laundry.



**O-SERIES:
THE PRECISION
YOU NEED TO GET
YOUR LAUNDRY
DONE RIGHT.**

ULTIMATE FLEXIBILITY

With the ability to program 100 unique cycles comprised of up to 20 distinct stages with many setting options, our controls offer the flexibility and precision you need to ensure your laundry is handled properly.

MULTI-LINGUAL OPTIONS

Our controls can be set for multiple languages either globally or for specific cycles. This means you could create cycles for your English-speaking employees and your employees that speak other languages, reducing the risk of misunderstanding.

MANAGEMENT REPORTING

Keep an eye on the productivity of your laundry room with our Total Control reporting options. Track machine downtime and cycle usage to ensure your laundry is running efficiently.

MOISTURE DETECTION SYSTEM

Our patented moisture detection system with wireless sensing technology takes the guess-work out of drying. Each auto dry cycle automatically stops when the load is dry, increasing throughput and reducing linen wear.

EASY PROGRAMMING WITH DEXTERLIVE

DexterLive.com makes it easier than ever to program your controls and manage your laundry. This free web application allows you to create and adjust all of your cycle settings. Your settings can then be downloaded and copied to your machines via USB.

SPECIALTY CYCLES

Our controls can be programmed for special cycles, such as ultra-delicate for wet cleaning. Plus, our 10-port chemical injection system allows for the right combination at the right time.

FIRE RESPONSE SYSTEM

All O-Series dryers offer the added safety of our Fire Response System by automatically sensing when a load is unexpectedly increasing in temperature. Water-based Fire Response models are also available.

INDUSTRY SETTINGS

Dirty laundry is common, but your specific needs are unique. Our controls offer cycles created specifically for certain industries. Whether you run a hotel, vet clinic, or nursing home, our control has the preset options you need to handle your laundry.

HEATED WASHERS

For applications where precision is critical, we offer heated washers that give real-time temperature feedback to ensure every load reaches its target temperature.

WASHERS Built to Last | Energy Efficient | 10-Year Warranty



EXPRESS DRYERS Built to Last | Superior Performance | 5-Year Warranty



EXPRESS STACK WASHER-DRYERS Built to Last | Superior Performance



EXPRESS WASHERS Built to Last | High Extract | 10-Year Warranty



EXPRESS O-SERIES WASHERS Total Control | High Extract | Ultimate Flexibility | 10-Year Warranty



EXPRESS O-SERIES DRYERS Total Control | Moisture Detection | Fire Response | 5-Year Warranty





EXPRESS O-SERIES WASHER SPECIFICATIONS

		T-350		T-450		T-650		T-750		T-950		T-1450		
Capacity	Dry Weight Capacity - lb (kg)		20	(9.1)	30	(13.6)	40	(18.1)	50	(22.7)	60	(27.2)	90	(40.8)
	Cylinder Volume - cu ft (L)		2.7	(76.5)	3.8	(107.6)	6	(170)	6.5	(184.1)	9	(254.9)	13.7	(388)
Speed	Maximum Extract Speed - g (RPM)		200	(819)	200	(750)	200	(750)	200	(685)	200	(685)	200	(617)
	Motor Size - hp (kW)		1	(0.75)	2	(1.5)	2	(1.5)	3	(2.2)	3	(2.2)	6.7	(5)
Dimensions	Cabinet Height - in (cm)		43 7/8	(111.4)	48 3/16	(122.4)	53	(134.6)	55 3/8	(140.7)	55 3/8	(140.7)	62 3/8	(158.4)
	Cabinet Width - in (cm)		26	(66)	29 7/8	(75.9)	29 7/8	(75.9)	34 3/8	(87.3)	34 3/8	(87.3)	41 1/2	(105.4)
	Cabinet Depth - in (cm)		28	(71.1)	28 1/4	(71.8)	38 1/8	(96.8)	32 7/8	(83.5)	38 7/8	(98.7)	42 1/4	(107.3)
	Door Opening - in (cm)		12 1/4	(31.1)	15 1/4	(38.7)	15 1/4	(38.7)	19 1/4	(48.9)	19 1/4	(48.9)	19 1/4	(48.9)
	Floor to Door Bottom - in (cm)		14 7/8	(37.8)	16 1/4	(41.3)	16 1/4	(41.3)	16	(40.6)	16	(40.6)	19 5/16	(49.1)
	Cylinder Diameter - in (cm)		21	(53.3)	25	(63.5)	25	(63.5)	30	(76.2)	30	(76.2)	37	(94)
	Cylinder Depth - in (cm)		13 1/2	(34.3)	13 3/8	(34)	21 1/8	(53.7)	16	(40.6)	22	(55.9)	22	(55.9)
Weight	Net Weight - lb (kg)		383	(173.7)	526	(238.6)	744	(337.5)	925	(419.6)	1000	(453.6)	1322	(599.6)
Shipping	Shipping Weight - lb (kg)		407	(184.6)	544	(246.8)	766	(347.5)	952	(431.8)	1016	(460.8)	1364	(618.7)
	Shipping Height - in (cm)		49 1/4	(125.1)	53 1/4	(135.3)	58 3/4	(149.2)	61 1/2	(156.2)	61 1/2	(156.2)	69 1/4	(175.9)
	Shipping Width - in (cm)		28 1/4	(71.8)	31 1/2	(80)	31 1/2	(80)	36	(91.4)	36	(91.4)	43 1/8	(109.5)
	Shipping Depth - in (cm)		33 1/2	(85.1)	33 1/2	(85.1)	43 3/4	(111.1)	38	(96.5)	45 1/4	(114.9)	48	(121.9)
Water	Water Inlet Size - in (mm)		3/4	(19)	3/4	(19)	3/4	(19)	3/4	(19)	3/4	(19)	3/4	(19)
	Pressure (min/max) - psi (kPa)		30-120	(207-827)	30-120	(207-827)	30-120	(207-827)	30-120	(207-827)	30-120	(207-827)	30-120	(207-827)
	Flow Rate - gal/min (L/min)		9	(34)	9	(34)	9	(34)	9	(34)	9 & 12	(34 & 45)	9 & 12	(34 & 45)
	Drain Diameter (O.D.) - in (cm)		2 1/4	(5.7)	3	(7.6)	3	(7.6)	3	(7.6)	3	(7.6)	3	(7.6)
	Floor to Center of Drain - in (cm)		6	(15.2)	5	(12.7)	6 7/8	(17.5)	6 5/8	(16.8)	6 5/8	(16.8)	8 5/16	(21.1)
Electrical	Model	Volts / Hz / Phase / Wiring	Circuit Breaker Amps / Running Amps / Wire Size											
	-12	208-240 / 60 / 1 / 2 wire + ground	15 / 6.2 / #12	15 / 6.2 / #12	15 / 6.2 / #12	20 / 8.4 / #12	20 / 12 / #12	30 / 15 / #10						
		208-240 / 60 / 3 / 3 wire + ground												
	-13	208-240 / 60 / 3 / 3 wire + ground	---	---	40 / 40 / #8	---	60 / 60 / #6	60 / 60 / #4						
	-39	230 / 50 / 1 / 2 wire + ground	15 / 6.2 / 3.5 mm²	15 / 6.2 / 3.5 mm²	15 / 6.2 / 3.5 mm²	20 / 8.4 / 3.5 mm²	20 / 12 / 3.5 mm²	30 / 15 / 5.3 mm²						
	-68	400 / 50 / 3 / 4 wire + ground	---	---	30 / 30 / 8.4 mm²	---	40 / 40 / 8.4 mm²	---						
Installation	Min. Clearance Between Machines - in (cm)		1/2	(1.3)	1/2	(1.3)	1/2	(1.3)	1/2	(1.3)	1/2	(1.3)	1/2	(1.3)
	Min. Clearance Behind Machines - in (cm)		24	(61)	24	(61)	24	(61)	24	(61)	24	(61)	24	(61)
	Min. Concrete Thickness - in (cm)		6	(15.2)	6	(15.2)	8	(20.3)	8	(20.3)	8	(20.3)	12	(30.5)
Options	Controls		O-Series		O-Series		O-Series		O-Series		O-Series		O-Series	

Due to continuous product improvements specifications are subject to change, please consult Dexter Laundry, your Dexter Authorized Distributor or the installation manual for the most accurate information. Agency approvals vary based on machine configuration. Major approval bodies include ETL, CE and AGA.

WASHER CONTROL COMPARISON

	6-Cycle	O-Series
MODEL CONFIGURATIONS		
HIGH EXTRACT SPEED	X	X
HEATED WATER OPTION (AVAILABILITY VARIES BY MODEL)		X
CONTROL PROGRAMMING		
PROGRAMMABLE CYCLES	6	100
PROGRAMMABLE STAGES	8	20
CHEMICAL INJECTION PORTS	4	10
SOAK OPTION		X
MULTIPLE AGITATION OPTIONS		X
DELAYED START		X
PROGRAMMABLE SPIN SPEEDS		X
DEXTERLIVE PROGRAMMING		X
CONTROL DISPLAY		
DISPLAY TYPE	SEGMENTED	FULL COLOR
MULTI-LINGUAL		X
PRODUCTIVITY REPORTING		X
TEMPERATURE RECORDING (AVAILABILITY VARIES BY MODEL)		X

DRYER CONTROL COMPARISON

	6-Cycle	O-Series
MODEL CONFIGURATIONS		
REVERSING TUMBLERS (AVAILABILITY VARIES BY MODEL)	X	X
MOISTURE DETECTION SYSTEM		X
FIRE RESPONSE SYSTEM		X
WATER-BASED FIRE RESPONSE SYSTEM		X
CONTROL PROGRAMMING		
PROGRAMMABLE CYCLES	6	100
PROGRAMMABLE STAGES	2	20
NO HEAT OPTION	X	X
PROGRAMMABLE REVERSING DELAY		X
DEXTERLIVE PROGRAMMING		X
CONTROL DISPLAY		
DISPLAY TYPE	SEGMENTED	FULL COLOR
MULTI-LINGUAL		X
PRODUCTIVITY REPORTING		X

6-CYCLE WASHER SPECIFICATIONS

		T-300		T-400		T-600		T-900		T-1200		
Capacity	Dry Weight Capacity - lb (kg)	20	(9.1)	30	(13.6)	40	(18.1)	60	(27.2)	80	(36.3)	
	Cylinder Volume - cu ft (L)	2.7	(76.5)	4	(113.3)	6	(170)	9	(254.9)	11.5	(325.6)	
Speed	High Extract Speed - g (RPM)	100	(579)	100	(532)	100	(532)	100	(485)	100	(485)	
	Motor Size - hp (kW)	1	(0.75)	2	(1.5)	2	(1.5)	3	(2.2)	3	(2.2)	
Dimensions	Cabinet Height - in (cm)	43 7/8	(111.4)	48 3/16	(122.4)	49 11/16	(126.2)	55 3/8	(140.7)	57 7/8	(147)	
	Cabinet Width - in (cm)	26	(66)	29 7/8	(75.9)	29 7/8	(75.9)	34 3/8	(87.3)	34 3/8	(87.3)	
	Cabinet Depth - in (cm)	25	(63.5)	27 3/8	(69.5)	36	(91.4)	38 7/8	(98.8)	45 3/8	(115.3)	
	Door Opening - in (cm)	12 1/4	(31.1)	15 1/4	(38.7)	15 1/4	(38.7)	19 1/4	(48.9)	19 1/4	(48.9)	
	Floor to Door Bottom - in (cm)	14 7/8	(37.8)	16 1/4	(41.3)	16 1/4	(41.3)	16	(40.6)	18 1/2	(47)	
	Cylinder Diameter - in (cm)	21	(53.3)	25	(63.5)	25	(63.5)	30	(76.2)	30	(76.2)	
	Cylinder Depth - in (cm)	13 1/2	(34.3)	14 1/8	(35.9)	21 1/8	(53.7)	22	(55.9)	28	(71.1)	
Weight	Net Weight - lb (kg)	317	(143.8)	432	(196)	558	(253.1)	964	(437.3)	1022	(463.6)	
Shipping	Shipping Weight - lb (kg)	340	(154.2)	450	(204.1)	580	(263.1)	980	(444.5)	1063	(482.2)	
	Shipping Height - in (cm)	50	(127)	53 1/4	(135.3)	54 3/4	(139.1)	61 1/2	(156.2)	63 3/4	(161.9)	
	Shipping Width - in (cm)	27 1/4	(69.2)	31 1/2	(80)	31 1/2	(80)	36	(91.4)	36	(91.4)	
	Shipping Depth - in (cm)	30 1/2	(77.5)	33 1/2	(85.1)	41	(104.1)	44 1/4	(112.4)	52 3/16	(132.6)	
Water	Water Inlet Size - in (mm)	3/4	(19)	3/4	(19)	3/4	(19)	3/4	(19)	3/4	(19)	
	Pressure (min/max) - psi (kPa)	30-120	(207-827)	30-120	(207-827)	30-120	(207-827)	30-120	(207-827)	30-120	(207-827)	
	Flow Rate - gal/min (L/min)	9	(34)	9	(34)	9	(34)	9	(34)	9 & 12	(34 & 45)	
	Drain Diameter (O.D.) - in (cm)	2 1/4	(5.7)	3	(7.6)	3	(7.6)	3	(7.6)	3	(7.6)	
	Floor to Center of Drain - in (cm)	6	(15.2)	4 11/16	(11.9)	5	(12.7)	6 5/8	(16.8)	8 5/8	(21.8)	
Electrical	Model	Volts / Hz / Phase / Wiring		Circuit Breaker Amps / Running Amps / Wire Size								
	-10	120 / 60 / 1 / Provided		20 / 13 / Provided	---		---		---		---	
	-12	208-240 / 60 / 1 / 2 wire + ground		15 / 4 / #12	15 / 6.2 / #12	15 / 6.2 / #12	20 / 8.4 / #12	20 / 8.4 / #12				
		208-240 / 60 / 3 / 3 wire + ground										
	-39	230 / 50 / 1 / 2 wire + ground		15 / 4 / 3.5 mm²	15 / 6.2 / 3.5 mm²	15 / 6.2 / 3.5 mm²	20 / 8.4 / 3.5 mm²	20 / 8.4 / 3.5 mm²				
	-59	230 / 50 / 1 / 2 wire + ground		15 / 4 / 3.5 mm²	15 / 6.2 / 3.5 mm²	15 / 6.2 / 3.5 mm²	20 / 8.4 / 3.5 mm²	---				
Installation	Min. Clearance Between Machines - in (cm)	1/2	(1.3)	1/2	(1.3)	1/2	(1.3)	1/2	(1.3)	1/2	(1.3)	
	Min. Clearance Behind Machines - in (cm)	24	(61)	24	(61)	24	(61)	24	(61)	24	(61)	
	Min. Concrete Thickness - in (cm)	6	(15.2)	6	(15.2)	6	(15.2)	8	(20.3)	8	(20.3)	
Options	Controls	6-Cycle Only		6-Cycle Only		6-Cycle Only		6-Cycle Only		6-Cycle Only		

Due to continuous product improvements specifications are subject to change, please consult Dexter Laundry, your Dexter Authorized Distributor or the installation manual for the most accurate information. Agency approvals vary based on machine configuration. Major approval bodies include ETL, CE and AGA.

EXPRESS 6-CYCLE WASHER SPECIFICATIONS

		T-350		T-450		T-650		T-750		T-950		T-1450	
Capacity	Dry Weight Capacity - lb (kg)	20	(9.1)	30	(13.6)	40	(18.1)	50	(22.7)	60	(27.2)	90	(40.8)
	Cylinder Volume - cu ft (L)	2.7	(76.5)	3.8	(107.6)	6	(170)	6.5	(184.1)	9	(254.9)	13.7	(388)
Speed	High Extract Speed - g (RPM)	200	(819)	200	(750)	200	(750)	200	(685)	200	(685)	200	(617)
	Motor Size - hp (kW)	1	(0.75)	2	(1.5)	2	(1.5)	3	(2.2)	3	(2.2)	6.7	(5)
Dimensions	Cabinet Height - in (cm)	43 7/8	(111.4)	48 3/16	(122.4)	53	(134.6)	55 3/8	(140.7)	55 3/8	(140.7)	62 3/8	(158.4)
	Cabinet Width - in (cm)	26	(66)	29 7/8	(75.9)	29 7/8	(75.9)	34 3/8	(87.3)	34 3/8	(87.3)	41 1/2	(105.4)
	Cabinet Depth - in (cm)	28	(71.1)	28 1/4	(71.8)	38 1/8	(96.8)	32 7/8	(83.5)	38 7/8	(98.7)	42 1/4	(107.3)
	Door Opening - in (cm)	12 1/4	(31.1)	15 1/4	(38.7)	15 1/4	(38.7)	19 1/4	(48.9)	19 1/4	(48.9)	19 1/4	(48.9)
	Floor to Door Bottom - in (cm)	14 7/8	(37.8)	16 1/4	(41.3)	16 1/4	(41.3)	16	(40.6)	16	(40.6)	19 5/16	(49.1)
	Cylinder Diameter - in (cm)	21	(53.3)	25	(63.5)	25	(63.5)	30	(76.2)	30	(76.2)	37	(94)
	Cylinder Depth - in (cm)	13 1/2	(34.3)	13 3/8	(34)	21 1/8	(53.7)	16	(40.6)	22	(55.9)	22	(55.9)
Weight	Net Weight - lb (kg)	383	(173.7)	526	(238.6)	744	(337.5)	925	(419.6)	1000	(453.6)	1322	(599.6)
Shipping	Shipping Weight - lb (kg)	407	(184.6)	544	(246.8)	766	(347.5)	952	(431.8)	1016	(460.8)	1364	(618.7)
	Shipping Height - in (cm)	49 1/4	(125.1)	53 1/4	(135.3)	58 3/4	(149.2)	61 1/2	(156.2)	61 1/2	(156.2)	69 1/4	(175.9)
	Shipping Width - in (cm)	28 1/4	(71.8)	31 1/2	(80)	31 1/2	(80)	36	(91.4)	36	(91.4)	43 1/8	(109.5)
	Shipping Depth - in (cm)	33 1/2	(85.1)	33 1/2	(85.1)	43 3/4	(111.1)	38	(96.5)	45 1/4	(114.9)	48	(121.9)
Water	Water Inlet Size - in (mm)	3/4	(19)	3/4	(19)	3/4	(19)	3/4	(19)	3/4	(19)	3/4	(19)
	Pressure (min/max) - psi (kPa)	30-120	(207-827)	30-120	(207-827)	30-120	(207-827)	30-120	(207-827)	30-120	(207-827)	30-120	(207-827)
	Flow Rate - gal/min (L/min)	9	(34)	9	(34)	9	(34)	9	(34)	9 & 12	(34 & 45)	9 & 12	(34 & 45)
	Drain Diameter (O.D.) - in (cm)	2 1/4	(5.7)	3	(7.6)	3	(7.6)	3	(7.6)	3	(7.6)	3	(7.6)
	Floor to Center of Drain - in (cm)	6	(15.2)	5	(12.7)	6 7/8	(17.5)	6 5/8	(16.8)	6 5/8	(16.8)	8 5/16	(21.1)
Electrical	Model	Volts / Hz / Phase / Wiring	Circuit Breaker Amps / Running Amps / Wire Size										
	-12	208-240 / 60 / 1 / 2 wire + ground	15 / 6.2 / #12	15 / 6.2 / #12	15 / 6.2 / #12	20 / 8.4 / #12	20 / 12 / #12	30 / 15 / #10					
		208-240 / 60 / 3 / 3 wire + ground											
	-39	230 / 50 / 1 / 2 wire + ground	15 / 6.2 / 3.5 mm²	15 / 6.2 / 3.5 mm²	15 / 6.2 / 3.5 mm²	20 / 8.4 / 3.5 mm²	20 / 12 / 3.5 mm²	30 / 15 / 5.3 mm²					
-59	230 / 50 / 1 / 2 wire + ground	15 / 6.2 / 3.5 mm²	15 / 6.2 / 3.5 mm²	15 / 6.2 / 3.5 mm²	20 / 8.4 / 3.5 mm²	---	---						
Installation	Min. Clearance Between Machines - in (cm)	1/2	(1.3)	1/2	(1.3)	1/2	(1.3)	1/2	(1.3)	1/2	(1.3)	1/2	(1.3)
	Min. Clearance Behind Machines - in (cm)	24	(61)	24	(61)	24	(61)	24	(61)	24	(61)	24	(61)
	Min. Concrete Thickness - in (cm)	6	(15.2)	6	(15.2)	8	(20.3)	8	(20.3)	8	(20.3)	12	(30.5)
Options	Controls	6-Cycle		6-Cycle		6-Cycle		6-Cycle		6-Cycle		6-Cycle	

Due to continuous product improvements specifications are subject to change, please consult Dexter Laundry, your Dexter Authorized Distributor or the installation manual for the most accurate information. Agency approvals vary based on machine configuration. Major approval bodies include ETL, CE and AGA.

		T-30		T-50	
Capacity	Dry Weight Capacity - lb (kg)	30	(13.6)	50	(22.7)
	Cylinder Volume - cu ft (L)	11.3	(320)	15.8	(447.4)
Speed & Airflow	Tumbler Speed - RPM	47	---	45	---
	Motor Size - Non-Reversing - 60 Hz : 50 Hz - hp (kW)	0.5 : 0.5	(0.38 : 0.38)	1 : 0.75	(0.75 : 0.56)
	Motor Size - Reversing - 60 Hz : 50 Hz - hp (kW)	---	---	2 & 0.5 : ---	(1.5 & 0.38 : ---)
	Airflow 8” Outlet - 60 Hz : 50 Hz - cfm (M3/min)	830 : 690	(23.5 : 19.5)	910 : 760	(25.8 : 21.5)
Dimensions & Weight	Cabinet Height - in (cm)	72 1/4	(183.5)	72 1/4	(183.5)
	Cabinet Width - in (cm)	31 1/2	(80)	34 1/2	(87.6)
	Cabinet Depth - Non-Reversing : Reversing - in (cm)	41 3/4 : ---	(106) : ---	48 : 50	(121.9 : 127)
	Door Opening - in (cm)	22 5/8	(57.5)	25 5/8	(65.1)
	Floor to Door Bottom - in (cm)	28 3/4	(73)	27 1/4	(69.2)
	Cylinder Diameter - in (cm)	30	(76.2)	32 1/2	(82.6)
	Cylinder Depth - in (cm)	27 1/2	(69.9)	33	(83.8)
	Lint Screen Area - sq in (sq cm)	515	(3323)	708	(4568)
Shipping	Net Weight - Non-Reversing : Reversing - lb (kg)	454 : ---	(205.9) : ---	540 : 560	(244.9 : 254)
	Shipping Weight - Non-Reversing : Reversing - lb (kg)	499 : ---	(226.3) : ---	590 : 620	(267.6 : 281.2)
	Shipping Height - in (cm)	77 1/4	(196.2)	77 1/4	(196.2)
	Shipping Width - in (cm)	32 3/4	(83.2)	36	(91.4)
Gas	Shipping Depth - Non-Reversing : Reversing - in (cm)	45 1/2	(115.6)	51 1/2 : 53 1/2	(130.8 : 135.9)
	Gas Supply Connection - in (mm)	1/2	(12.7)	1/2	(12.7)
	Natural Gas Supply (Water Column) - in (cm)	5-8	(12.7-20.3)	5-8	(12.7-20.3)
	LP Gas Supply (Water Column) - in (cm)	11 1/2-13 1/2	(29.2-34.3)	11 1/2-13 1/2	(29.2-34.3)
Electrical	Gas Usage - 60Hz : 50 Hz - BTU/hr (kW)	90,000 : 74,000	(26.4 : 21.7)	145,000 : 120,000	(42.5 : 35.2)
	Gas Models	Volts / Hz / Phase / Wiring		Circuit Breaker Amps / Running Amps / Wire Size / Reversing Availability	
	-11	208-240 / 60 / 1 / 2 wire + ground		---	
	-15	208-240 / 60 / 1 / 2 wire + ground		15 / 5.1 / #12 / Non-Reversing	
Installation	-15	120 / 60 / 1 / 2 wire + ground		15 / 9.6 / #12 / Non-Reversing	
	-39	230 / 50 / 1 / 2 wire + ground		10 / 5.1 / 2.1 mm² / Non-Reversing	
Options	Minimum Clearance Between Machines - in (cm)	0	(0)	0	(0)
	Minimum Clearance Behind Machines - in (cm)	18	(45.7)	18	(45.7)
	Make-Up Air Required - sq ft (sq cm)	1	(929)	1.25	(1161)
	Exhaust Size - in (cm)	8	(20.3)	8	(20.3)
	Max. Exhaust Back Pressure (Water Column) - in (mm)	0.3	(7.6)	0.3	(7.6)
	Recommended Exhaust Length - ft (m) & 2 elbows	14	(4.3)	14	(4.3)
Options	Controls	O-Series		O-Series	
	Reversing	---		Option	
	Other Features & Options	Moisture Detection, Fire Response System		Moisture Detection, Fire Response	

Due to continuous product improvements specifications are subject to change, please consult Dexter Laundry, your Dexter Authorized Distributor or the installation manual for the most accurate information. Agency approvals vary based on machine configuration. Major approval bodies include ETL, CE and AGA.

		T-80		T-120	
Capacity	Dry Weight Capacity - lb (kg)	80	(36.3)	120	(54.4)
	Cylinder Volume - cu ft (L)	23	(651.3)	36.1	(1022.2)
Speed	Tumbler Speed - RPM	40	---	36.5	---
	Motor Size - Non-Reversing - 60 Hz : 50 Hz - hp (kW)	1 : 0.75	(0.75 : 0.56)	---	---
	Motor Size - Reversing - 60 Hz : 50 Hz - hp (kW)	1 & 0.75 : 1 & 0.75	(0.75 & 0.56 : 0.75 & 0.56)	1 & 1 : 1 & 0.75	(0.75 & 0.75 : 0.75 & 0.56)
Airflow	Airflow 8” Outlet - 60 Hz : 50 Hz - cfm (M3/min)	1200 : 1000	(34 : 28.3)	---	---
	Airflow 10” Outlet - 60 Hz & 50 Hz - cfm (M3/min)	---	---	1250 : 1000	(35.4 : 28.3)
	Airflow 12” Outlet - 60 Hz & 50 Hz - cfm (M3/min)	---	---	1450 : 1000	(41.1 : 28.3)
Dimensions & Weight	Cabinet Height - in (cm)	75 3/4	(192.4)	85 5/16	(216.7)
	Cabinet Width - in (cm)	38 1/2	(97.8)	46 3/4	(188.7)
	Cabinet Depth - in (cm)	51 3/4	(131.4)	60 3/16	(152.9)
	Door Opening - in (cm)	25 5/8	(65.1)	30	(76.2)
	Floor to Door Bottom - in (cm)	29 1/4	(74.3)	34	(86.4)
	Cylinder Diameter - in (cm)	36 1/2	(92.7)	43	(109.2)
	Cylinder Depth - in (cm)	38	(96.5)	43	(109.2)
	Lint Screen Area - sq in (sq cm)	823	(5310)	862	(5561)
	Net Weight - lb (kg)	715	(324.3)	1075	(487.6)
Shipping	Shipping Weight - lb (kg)	770	(349.3)	1122	(508.9)
	Shipping Height - in (cm)	80 3/4	(205.1)	88 3/8	(224.5)
	Shipping Width - in (cm)	40 1/4	(102.2)	48 1/4	(122.6)
	Shipping Depth - in (cm)	55 1/2	(141)	68 1/2	(174)
Gas	Gas Supply Connection - in (mm)	3/4	(19.1)	3/4	(19.1)
	Natural Gas Supply (Water Column) - in (cm)	5-8	(12.7-20.3)	5-8	(12.7-20.3)
	LP Gas Supply (Water Column) - in (cm)	11 1/2-13 1/2	(29.2 - 34.3)	11 1/2-13 1/2	(29.2-34.3)
	Gas Usage - 60Hz : 50 Hz - BTU/hr (kW)	215,000 : 195,000	(63 : 57.1)	320,000 : 300,000	(93.8 : 87.9)
Electrical	Gas Models	Volts / Hz / Phase / Wiring		Circuit Breaker Amps / Running Amps / Wire Size / Reversing Availability	
	-10	120 / 60 / 1 / 2 wire + ground		15 / 10.4 / #12 / Reversing	
	-11	208-240 / 60 / 1 / 2 wire + ground		15 / 5.5 / #12 / Reversing	
	-15	208-240 / 60 / 1 / 2 wire + ground		15 / 5.5 / #12 / Non-Reversing	
	-15	120 / 60 / 1 / 2 wire + ground		15 / 10.4 / #12 / Non-Reversing	
	-39	230 / 50 / 1 / 2 wire + ground		10 / 5.2 / 2.1 mm² / Reversing & Non-Reversing	
Installation	Minimum Clearance Between Machines - in (cm)	0	(0)	0	(0)
	Minimum Clearance Behind Machines - in (cm)	18	(45.7)	18	(45.7)
	Make-Up Air Required - sq ft (sq cm)	1.5	(1394)	2.25	(2090)
	Exhaust Size - in (cm)	8	(20.3)	10 or 12	(25.4 or 30.5)
	Max. Exhaust Back Pressure (Water Column) - in (mm)	0.3	(7.6)	0.3	(7.6)
	Recommended Exhaust Length - ft (m) & 2 elbows	14	(4.3)	14	(4.3)
Options	Controls	O-Series		O-Series	
	Reversing	Option		Standard	
	Other Features & Options	Moisture Detection, Fire Response		Moisture Detection, Fire Response	

Due to continuous product improvements specifications are subject to change, please consult Dexter Laundry, your Dexter Authorized Distributor or the installation manual for the most accurate information. Agency approvals vary based on machine configuration. Major approval bodies include ETL, CE and AGA.

EXPRESS 6-CYCLE DRYER SPECIFICATIONS

		T-30		T-50	
Capacity	Dry Weight Capacity - lb (kg)	30	(13.6)	50	(22.7)
	Cylinder Volume - cu ft (L)	11.3	(320)	15.8	(447.4)
Speed & Airflow	Tumbler Speed - RPM	47	---	45	---
	Motor Size - Non-Reversing - 60 Hz : 50 Hz - hp (kW)	0.5 : 0.5	(0.38 : 0.38)	1 : 0.75	(0.75 : 0.56)
	Motor Size - Reversing - 60 Hz : 50 Hz - hp (kW)	---	---	2 & 0.5 : ---	(1.5 & 0.38 : ---)
	Airflow 8" Outlet - 60 Hz : 50 Hz - cfm (M3/min)	830 : 690	(23.5 : 19.5)	910 : 760	(25.8 : 21.5)
Dimensions & Weight	Cabinet Height - in (cm)	72 1/4	(183.5)	72 1/4	(183.5)
	Cabinet Width - in (cm)	31 1/2	(80)	34 1/2	(87.6)
	Cabinet Depth - Non-Reversing : Reversing - in (cm)	41 3/4 : ---	(106 : ---)	48 : 50	(121.9 : 127)
	Door Opening - in (cm)	22 5/8	(57.5)	25 5/8	(65.1)
	Floor to Door Bottom - in (cm)	28 3/4	(73)	27 1/4	(69.2)
	Cylinder Diameter - in (cm)	30	(76.2)	32 1/2	(82.6)
	Cylinder Depth - in (cm)	27 1/2	(69.9)	33	(83.8)
	Lint Screen Area - sq in (sq cm)	515	(3323)	708	(4568)
	Net Weight - Non-Reversing : Reversing - lb (kg)	454 : ---	(205.9 : ---)	540 : 560	(244.9 : 254)
Shipping	Shipping Weight - Non-Reversing : Reversing - lb (kg)	499 : ---	(226.3 : ---)	590 : 620	(267.6 : 281.2)
	Shipping Height - in (cm)	77 1/4	(196.2)	77 1/4	(196.2)
	Shipping Width - in (cm)	32 3/4	(83.2)	36	(91.4)
	Shipping Depth - Non-Reversing : Reversing - in (cm)	45 1/2 : ---	(115.6 : ---)	51 1/2 : 53 1/2	(130.8 : 135.9)
Gas	Gas Supply Connection - in (mm)	1/2	(12.7)	1/2	(12.7)
	Natural Gas Supply (Water Column) - in (cm)	5-8	(12.7-20.3)	5-8	(12.7-20.3)
	LP Gas Supply (Water Column) - in (cm)	11 1/2-13 1/2	(29.2-34.3)	11 1/2-13 1/2	(29.2-34.3)
	Gas Usage - 60Hz : 50 Hz - BTU/hr (kW)	90,000 : 74,000	(26.4 : 21.7)	145,000 : 120,000	(42.5 : 35.2)
Electrical	Gas Models	Volts / Hz / Phase / Wiring	Circuit Breaker Amps / Running Amps / Wire Size / Reversing Availability		
	-10	120 / 60 / 1 / 2 wire + ground	15 / 9.6 / #12 / Non-Reversing		15 / 9.6 / #12 / Non-Reversing
	-11	208-240 / 60 / 1 / 2 wire + ground	---		15 / 5.1 / #12 / Reversing
	-39	230 / 50 / 1 / 2 wire + ground	10 / 5.1 / 2.1 mm² / Non-Reversing		10 / 5.1 / 2.1 mm² / Non-Reversing
	-59	230 / 50 / 1 / 2 wire + ground	10 / 5.1 / 2.1 mm² / Non-Reversing		10 / 5.1 / 2.1 mm² / Non-Reversing
	Electric Models	kW / Volts / Hz / Phase / Wiring	Circuit Breaker Amps / Running Amps / Wire Size / Reversing Availability		
	-71	24 / 208 / 60 / 3 / 4 wire + ground	90 / 85 / #2 / Non-Reversing		90 / 85 / #2 / Non-Reversing
	-72	30 / 208 / 60 / 3 / 4 wire + ground	---		100 / 100 / #1 / Non-Reversing
	-74	24 / 240 / 60 / 3 / 4 wire + ground	80 / 75 / #3 / Non-Reversing		80 / 75 / #3 / Non-Reversing
	-75	30 / 240 / 60 / 3 / 4 wire + ground	---		90 / 90 / #2 / Non-Reversing
	-77	20 / 208 / 60 / 1 / 3 wire + ground	125 / 120 / (1/0) / Non-Reversing		---
	-78	20 / 240 / 60 / 1 / 3 wire + ground	110 / 105 / (1/0) / Non-Reversing		---
	-79	24 / 400 / 50 / 3 / 4 wire + ground	50 / 45 / 13.3 mm² / Non-Reversing		50 / 45 / 13.3 mm² / Non-Reversing
Installation	Minimum Clearance Between Machines - in (cm)	0	(0)	0	(0)
	Minimum Clearance Behind Machines - in (cm)	18	(45.7)	18	(45.7)
	Make-Up Air Required - sq ft (sq cm)	1	(929)	1.25	(1161)
	Exhaust Size - in (cm)	8	(20.3)	8	(20.3)
	Max. Exhaust Back Pressure (Water Column) - in (mm)	0.3	(7.6)	0.3	(7.6)
	Recommended Exhaust Length - ft (m) & 2 elbows	14	(4.3)	14	(4.3)
Options	Controls	6-Cycle		6-Cycle	
	Reversing	---		Option	

Due to continuous product improvements specifications are subject to change, please consult Dexter Laundry, your Dexter Authorized Distributor or the installation manual for the most accurate information. Agency approvals vary based on machine configuration. Major approval bodies include ETL, CE and AGA.

EXPRESS 6-CYCLE DRYER SPECIFICATIONS

		T-80		T-120	
Capacity	Dry Weight Capacity - lb (kg)	80	(36.3)	120	(54.4)
	Cylinder Volume - cu ft (L)	23	(651.3)	36.1	(1022.2)
Speed	Tumbler Speed - RPM	40	---	36.5	---
	Motor Size - Non-Reversing - 60 Hz : 50 Hz - hp (kW)	1 : 0.75	(0.75 : 0.56)	---	---
	Motor Size - Reversing - 60 Hz : 50 Hz - hp (kW)	1 & 0.75 : 1 & 0.75	(0.75 & 0.56 : 0.75 & 0.56)	1 & 1 : 1 & 0.75	(0.75 & 0.75 : 0.75 & 0.56)
Airflow	Airflow 8" Outlet - 60 Hz : 50 Hz - cfm (M3/min)	1200 : 1000	(34 : 28.3)	---	---
	Airflow 10" Outlet - 60 Hz & 50 Hz - cfm (M3/min)	---	---	1250 : 1000	(35.4 : 28.3)
	Airflow 12" Outlet - 60 Hz & 50 Hz - cfm (M3/min)	---	---	1450 : 1000	(41.1 : 28.3)
Dimensions & Weight	Cabinet Height - in (cm)	75 3/4	(192.4)	85 5/16	(216.7)
	Cabinet Width - in (cm)	38 1/2	(97.8)	46 3/4	(188.7)
	Cabinet Depth - in (cm)	51 3/4	(131.4)	60 3/16	(152.9)
	Door Opening - in (cm)	25 5/8	(65.1)	30	(76.2)
	Floor to Door Bottom - in (cm)	29 1/4	(74.3)	34	(86.4)
	Cylinder Diameter - in (cm)	36 1/2	(92.7)	43	(109.2)
	Cylinder Depth - in (cm)	38	(96.5)	43	(109.2)
	Lint Screen Area - sq in (sq cm)	823	(5310)	862	(5561)
	Net Weight - lb (kg)	715	(324.3)	1075	(487.6)
Shipping	Shipping Weight - lb (kg)	770	(349.3)	1122	(508.9)
	Shipping Height - in (cm)	80 3/4	(205.1)	88 3/8	(224.5)
	Shipping Width - in (cm)	40 1/4	(102.2)	48 1/4	(122.6)
	Shipping Depth - in (cm)	55 1/2	(141)	68 1/2	(174)
Gas	Gas Supply Connection - in (mm)	3/4	(19.1)	3/4	(19.1)
	Natural Gas Supply (Water Column) - in (cm)	5-8	(12.7-20.3)	5-8	(12.7-20.3)
	LP Gas Supply (Water Column) - in (cm)	11 1/2-13 1/2	(29.2 - 34.3)	11 1/2-13 1/2	(29.2-34.3)
	Gas Usage - 60Hz : 50 Hz - BTU/hr (kW)	215,000 : 195,000	(63 : 57.1)	320,000 : 300,000	(93.8 : 87.9)
Electrical	Gas Models	Volts / Hz / Phase / Wiring	Circuit Breaker Amps / Running Amps / Wire Size / Reversing Availability		
	-10	120 / 60 / 1 / 2 wire + ground	15 / 10.4 / #12 / Reversing & Non-Reversing		25 / 15 / #12 / Reversing
	-39	230 / 50 / 1 / 2 wire + ground	10 / 5.2 / 2.1 mm² / Reversing & Non-Reversing		20 / 10 / 3.5 mm² / Reversing
	-59	230 / 50 / 1 / 2 wire + ground	10 / 5.2 / 2.1 mm² / Non-Reversing		---
	Electric Models	kW / Volts / Hz / Phase / Wiring	Circuit Breaker Amps / Running Amps / Wire Size / Reversing Availability		
	-72	30 / 208 / 60 / 3 / 4 wire + ground	100 / 100 / #1 / Non-Reversing		---
	-73	35 / 208 / 60 / 3 / 4 wire + ground	125 / 120 / (1/0) / Non-Reversing		---
	-75	30 / 240 / 60 / 3 / 4 wire + ground	90 / 90 / #2 / Non-Reversing		---
	-76	36 / 240 / 60 / 3 / 4 wire + ground	110 / 105 / #1 / Non-Reversing		---
	-79	24 / 400 / 50 / 3 / 4 wire + ground	50 / 45 / 13.3 mm² / Non-Reversing		---
Installation	Minimum Clearance Between Machines - in (cm)	0	(0)	0	(0)
	Minimum Clearance Behind Machines - in (cm)	18	(45.7)	18	(45.7)
	Make-Up Air Required - sq ft (sq cm)	1.5	(1394)	2.25	(2090)
	Exhaust Size - in (cm)	8	(20.3)	10 or 12	(25.4 or 30.5)
	Max. Exhaust Back Pressure (Water Column) - in (mm)	0.3	(7.6)	0.3	(7.6)
	Recommended Exhaust Length - ft (m) & 2 elbows	14	(4.3)	14	(4.3)
Options	Controls	6-Cycle		6-Cycle	
	Reversing	Option		Standard	

Due to continuous product improvements specifications are subject to change, please consult Dexter Laundry, your Dexter Authorized Distributor or the installation manual for the most accurate information. Agency approvals vary based on machine configuration. Major approval bodies include ETL, CE and AGA.

EXPRESS 6-CYCLE STACK DRYER SPECIFICATIONS

			T-20x2		T-30x2		T-50x2	
Capacity	Dry Weight Capacity - lb (kg)		2 x 20	(2 x 9.1)	2 x 30	(2 x 13.6)	2 x 50	(2 x 22.7)
	Cylinder Volume (per tumbler) - cu ft (L)		7	(320)	11.3	(320)	15.8	(447.4)
Speed & Airflow	Tumbler Speed - RPM		51	---	47	---	45	---
	Motor Size (per tumbler) - Non-Reversing : Reversing: - hp (kW)		0.3 : ---	(0.38 : ---)	0.5 : ---	(0.38 : ---)	0.75 : 2 & 0.5	(0.56 : 1.5 & 0.38)
	Airflow - 60 Hz (per tumbler) - cfm (M3/min)		370	(10.5)	600	(17)	650	(18.4)
	Airflow - 50 Hz (per tumbler) - cfm (M3/min)		300	(8.5)	500	(14.2)	510	(14.4)
Dimensions & Weight	Cabinet Height - in (cm)		68 1/2	(174)	76 1/4	(193.7)	79 1/4	(201.3)
	Cabinet Width - in (cm)		27	(68.6)	31 1/2	(80)	34 1/2	(87.6)
	Cabinet Depth - in (cm)		44 5/8	(113.3)	49 1/2	(125.7)	54 3/4	(139.1)
	Door Opening - in (cm)		18 1/8	(46)	22 5/8	(57.5)	25 5/8	(65.1)
	Floor Door Bottom - Lower : Upper - in (cm)		8 1/2 : 42	(21.6 : 106.7)	7 5/8 : 45 1/4	(19.4 : 114.9)	7 : 46	(17.8 : 116.8)
	Cylinder Diameter - in (cm)		25 1/2	(64.8)	30	(76.2)	32 1/2	(82.6)
	Cylinder Depth - in (cm)		24	(61)	27 1/2	(69.9)	33	(83.8)
	Lint Screen Area (per tumbler) - sq in (sq cm)		285	(1839)	453	(2923)	544	(3510)
	Net Weight - lb (kg)		615	(279)	719	(326.1)	871	(395.1)
Shipping	Shipping Weight - lb (kg)		650	(295)	765	(347)	922	(418.2)
	Shipping Height - in (cm)		74	(188)	81 1/4	(206.4)	84 1/4	(214)
	Shipping Width - in (cm)		31.5	(80)	33	(83.8)	36	(91.4)
	Shipping Depth - in (cm)		49	(124.5)	57 3/4	(146.7)	61 1/2	(156.2)
Gas	Gas Supply Connection - in (mm)		1/2	(12.7)	1/2	(12.7)	1/2	(12.7)
	Natural Gas Supply (Water Column) - in (cm)		5-8	(12.7-20.3)	5-8	(12.7-20.3)	5-8	(12.7-20.3)
	LP Gas Supply (Water Column) - in (cm)		11 1/2 - 13 1/2	(29.2 - 34.3)	11 1/2 - 13 1/2	(29.2 - 34.3)	11 1/2 - 13 1/2	(29.2 - 34.3)
	Gas Usage - 60 Hz : 50 Hz (per tumbler) - BTU/hr (kW)		56,000 : 47,000	(16.4 : 13.8)	90,000 : 74,000	(26.4 : 21.7)	108,000 : 96,500	(31.7: 28.3)
Electrical	Gas Models (per stack dryer)	Volts / Hz / Phase / Wiring	Circuit Breaker Amps / Running Amps / Wire Size / Reversing Availability					
	-11	208-240 / 60 / 1 / 2 wire + ground	---		---		20 / 15 / #12 / Reversing	
	-15	208-240 / 60 / 1 / 2 wire + ground	15 / 3.8 / #12 / Non-Reversing		15 / 5 / #12 / Non-Reversing		20 / 10 / #12 / Non-Reversing	
		120 / 60 / 1 / 2 wire + ground	15 / 7.8 / #12 / Non-Reversing		20 / 8 / #12 / Non-Reversing		30 / 20 / #10 / Non-Reversing	
	-39	230 / 50 / 1 / 2 wire + ground	15 / 6.6 / 3.5 mm² / Non-Reversing		15 / 10 / 3.5 mm² / Non-Reversing		20 / 15 / 3.5 mm² / Reversing	
							20 / 10 / 3.5 mm² / Non-Reversing	
	-59	230 / 50 / 1 / 2 wire + ground	---		15 / 10 / 3.5 mm² / Non-Reversing		20 / 10 / 3.5 mm² / Non-Reversing	
	Dexter Stack Dryers are also available with electrical heat configurations. For more information please refer to DEXTER.COM or contact your Dexter Authorized Distributor.							
Installation	Minimum Clearance Between Machines - in (cm)		0	(0)	0	(0)	0	(0)
	Minimum Clearance Behind Machines - in (cm)		18	(45.7)	18	(45.7)	18	(45.7)
	Make-Up Air Required (per stack dryer) - sq ft (sq cm)		1	(929)	1.5	(1394)	1.5	(1394)
	Exhaust Size - in (cm)		8	(20.3)	8	(20.3)	8	(20.3)
	Max. Exhaust Back Pressure (Water Column) - in (mm)		0.3	(7.6)	0.3	(7.6)	0.3	(7.6)
	Recommended Exhaust Length - ft (m) & 2 elbows		14	(4.3)	14	(4.3)	14	(4.3)
Options	Controls		6-Cycle Only		6-Cycle Only		6-Cycle Only	
	Other Features & Options		---		---		Reversing	

Due to continuous product improvements specifications are subject to change, please consult Dexter Laundry, your Dexter Authorized Distributor or the installation manual for the most accurate information. Agency approvals vary based on machine configuration. Major approval bodies include ETL, CE and AGA.

EXPRESS 6-CYCLE STACK WASHER-DRYER SPECIFICATIONS

			T-350 SWD		T-450 SWD		T-750 SWD			
Capacity	Dry Weight Capacity (per machine) - lb (kg)		20	(9.1)	30	(13.6)	50	(22.7)		
	Cylinder Volume - Washer : Dryer - cu ft (L)		2.7 : 7	(76.5 : 198.2)	4 : 11.3	(113.3 : 320)	6.5 : 15.8	(184.1 : 447.4)		
Speed & Airflow	Washer Extract Speed - High - g (RPM)		200	(579)	200	(750)	200	(685)		
	Dryer Tumbler Speed - RPM		51	---	47	---	45	---		
	Motor Size - Washer : Dryer - hp (kW)		1 : ⅓	(0.75 : 0.25)	2 : ½	(1.5 : 0.38)	3 : 2 & ½	(2.2 : 1.5 & 0.38)		
	Airflow - 60 Hz : 50 Hz - cfm (M3/min)		370 : 300	(10.5 : 8.5)	500 : 450	(14.6 : 12.7)	650 : 510	(18.4 : 14.4)		
Dimensions	Overall - Height : Width : Depth - in (cm)		74 ¾ : 27 : 44 ⅝	(189.9 : 68.6 : 113.7)	78 ⅜ : 31 ½ : 49 ⅞	(199 : 80 : 125.6)	87 ⅜ : 34 ½ : 54 ⅝	(221.5 : 87.6 : 138.7)		
	Shipping - Height : Width : Depth - in (cm)		80 ⅝ : 29 ¼ : 49 ⅜	(204.8 : 74.3 : 126.4)	84 : 34 : 54	(213.4 : 86.4 : 137.2)	91 ⅝ : 35 ⅞ : 63 ½	(232.7 : 91.1 : 161.3)		
	Weight - Net : Shipping - lb (kg)		800 : 840	(362.9 : 381)	1051 : 1101	(476.7 : 499.4)	1600 : 1650	(725.7 : 748.4)		
	Washer Cylinder - Diameter : Depth - in (cm)		21 : 13 ½	(53.3 : 34.3)	25 : 14 ⅛	(63.5 : 35.9)	30 : 16	(76.2 : 40.6)		
	Dryer Cylinder - Diameter : Depth - in (cm)		25 ½ : 24	(64.8 : 61)	30 : 27 ½	(76.2 : 69.9)	32 ½ : 33	(82.5 : 83.8)		
	Door Opening - Washer : Dryer - in (cm)		12 ¼ : 18 ⅛	(31.1 : 46)	15 ¼ : 22 ⅞	(38.7 : 57.6)	19 ¼ : 25 ⅝	(48.9 : 65.1)		
	Floor to Door Bottom - Washer : Dryer - in (cm)		14 ⅞ : 48 ¼	(37.8 : 122.6)	12 ⅞ : 47 ⅜	(31.6 : 120.3)	16 : 55 ⅛	(40.6 : 140)		
	Dryer Lint Screen Area - sq in (sq cm)		285	(1839)	453	(2923)	544	(3510)		
Installation	Min. Clearance - Between : Behind - in (cm)		½ : 24	(1.3 : 61)	½ : 24	(1.3 : 61)	½ : 24	(1.3 : 61)		
	Min. Concrete Thickness - in (cm)		6	(15.2)	6	(15.2)	8	(20.3)		
	Make-Up Air Required - sq ft (sq cm)		0.7	(650)	1	(929)	1	(929)		
	Exhaust Size - in (cm)		6	(15.2)	6	(15.2)	8	(20.3)		
	Max. Exhaust Back Pressure (Water Column) - in (mm)		0.3	(7.6)	0.3	(7.6)	0.3	(7.6)		
	Recommended Exhaust Length - ft (m) & 2 elbows		14	(4.3)	14	(4.3)	14	(4.3)		
Water	Water Inlet Size - in (mm)		¾	(19)	¾	(19)	¾	(19)		
	Pressure (min-max) - psi (kPa)		30-120	(207-827)	30-120	(207-827)	30-120	(207-827)		
	Flow Rate - gal/min (L/min)		9	(34)	9	(34)	9	(34)		
	Drain Diameter (O.D.) - in (cm)		2 ¼	(5.7)	3	(7.6)	3	(7.6)		
	Floor to Center of Drain - in (cm)		5 ⅞	(14.9)	4 ⅞	(11.3)	6 ⅝	(16.8)		
Gas	Gas Supply Connection - in (mm)		½	(12.7)	½	(12.7)	½	(12.7)		
	Natural Gas Supply (Water Column) - in (cm)		5-8	(12.7-20.3)	5-8	(12.7-20.3)	5-8	(12.7-20.3)		
	LP Gas Supply (Water Column) - in (cm)		11 1/2 - 13 1/2	(29.2 - 34.3)	11 1/2 - 13 1/2	(29.2 - 34.3)	11 1/2 - 13 1/2	(29.2 - 34.3)		
	Gas Usage - 60 Hz : 50 Hz - BTU/hr (kW)		56,000 : 47,000	(16.4 : 13.8)	80,000 : 74,000	(23.4 : 21.7)	108,000 : 96,000	(31.7 : 28.3)		
Electrical	Model		Volts / Hz / Phase / Wiring		Circuit Breaker Amps / Running Amps / Wire Size / Dryer Reversing Availability					
	-16	Washer	208-240 / 60 / 1 / 2 wire + ground		---		---			
			208-240 / 60 / 3 / 3 wire + ground							
		Gas Dryer	208-240 / 60 / 1 / 2 wire + ground		---		15 / 10 / #12 / Reversing			
	-17	Washer	208-240 / 60 / 1 / 2 wire + ground						15 / 6.2 / #12	
			208-240 / 60 / 3 / 3 wire + ground							
		Gas Dryer	120 / 60 / 1 / 2 wire + ground		15 / 3.9 / #12 / Non-Reversing		15 / 4 / #12 / Non-Reversing		---	
			208-240 / 60 / 1 / 2 wire + ground		15 / 1.9 / #12 / Non-Reversing		15 / 2.5 / #12 / Non-Reversing		---	
	-39	Washer	230 / 50 / 1 / 2 wire + ground		15 / 6.2 / 3.5 mm²		15 / 6.5 / 3.5 mm²		20 / 8.4 / 3.5 mm²	
		Gas Dryer	230 / 50 / 1 / 3 wire + ground		15 / 3.4 / 3.5 mm² / Non-Reversing		15 / 5 / 3.5 mm² / Non-Reversing		15 / 10 / 3.5 mm² / Reversing	
	Dexter Stack Washer-Dryers are also available with electrical heat configurations. For more information please refer to DEXTER.COM or contact your Dexter Authorized Distributor.									
Options	Controls		6-Cycle Only		6-Cycle Only		6-Cycle Only			
	Other Features & Options		---		---		Reversing Standard			

Due to continuous product improvements specifications are subject to change, please consult Dexter Laundry, your Dexter Authorized Distributor or the installation manual for the most accurate information. Agency approvals vary based on machine configuration. Major approval bodies include ETL, CE and AGA.



DEXTER.
LAUNDRY

DEXTER.COM EMPLOYEE OWNED | MADE IN THE USA | SINCE 1894 **1.800.524.2954**

