



LOCATION: TOP FRONT

LOCATION: CONTROL TROUGH

LOCATION: BOTTOM

LOCATION: BACK

WIRING DIAGRAM 208-240V, 3/1PH, 60HZ

P/N 9506-708-001PR
 40# EXP OPL VF DRIVE, 208-240V
 WNO650XA-12_V_X-____X

WATER VALVES
 H2 - HOT SOAP
 H1 - HOT TUB
 C2 - COLD SOFTENER
 C1 - COLD TUB

INJECTOR CONNECTORS
 COM
 D
 C
 B
 A
 FL2
 FL1

100% AM
 WHT 10V RC
 M15 DCM M01
 M16 DCM M01
 M18 DCM M01
 M19 DCM M01
 REMOVE FOR 140C
 BRN M15
 M16 DCM M01
 M18 DCM M01
 M19 DCM M01

VARIABLE FREQUENCY DRIVE 1006
 WHT 10V RC
 YEL M15
 YEL DCM M01
 WHT M16
 WHT DCM M01
 BRN M18
 BRN DCM M01

PUSHBUTTONS
 UP
 DOWN
 START
 STOP
 ○ TIME REMAINING
 ○ READY FOR USE
 DISPLAY

RAPID ADVANCE / PROGRAM KEY SWITCH

WATER VALVES
 H2
 H1
 C2
 C1

208V-240V
 3/1PH-60HZ